

ROBERTS 5216 CARPET SEAM ADHESIVE



GENERAL DESCRIPTION:

Roberts 5216 is an extrudable solvent based neoprene contact type adhesive. This adhesive has good water and heat resistance.

FOR BONDING:

Carpet seam edges together where carpet is either directly bonded to the floor or double bonded over underlay.

STANDARD

AS/NZ Standard 2455.1:2007 "Textile Floor Covering – Installation Practice".

APPLICATION:

Apply a 3mm bead Roberts 5216 to the subfloor or double-bond underlay. Lay carpet seams into wet bead of adhesive.

CLEAN UP:

Suitable solvent cleaner/thinner for equipment and tools. Use extreme care when using any solvent cleaner on carpet, vinyl, etc.

TYPICAL PROPERTIES:

Appearance:	Honey like
Base:	Neoprene rubber
Solids:	22%
Carrier:	Hydrocarbon Solvent
Viscosity	1800 cps (approx)
Flammability:	Flammable
Toxicity:	Toxic
Specific Gravity:	0.90 (approx)
Shelf Life:	12 months in sealed container
Pack Size:	1L screw top tin

STORAGE:

Store in original containers out of direct sunlight, under cover and away from all sources of heat and ignition.

This product is classified:

UN 1133
D.G. Class 3
Hazchem 3 YE
Packaging Group II
...and is HIGHLY FLAMMABLE.

This product should be stored accordingly and in line with correct regulations.

SAFETY & HANDLING

Roberts 5216 is a flammable product. Good housekeeping and ventilation is essential. Avoid skin contact. Use in well ventilated areas. Keep away from ignition sources, sparks, and flames. Do not smoke when using. Do not use near heat sources or open flames.

HEALTH HAZARD & FIRST AID:

If poisoning occurs, contact a doctor or the Poisons Information Centre. If swallowed, DO NOT induce vomiting. Give a glass of water. For further information refer to the product Material Safety Data Sheet.

Warning: Intentional misuse by deliberately inhaling vapours can be harmful or fatal.

Material Safety Data Sheet available upon request.

Disclaimer: Information given on this data sheet is to the best available knowledge of the manufacturer, true and correct. However owing to the diverse nature of applications, conditions, and materials used, no guarantee either expressed or implied, can be given. Enquiries should be directed to DGL Bondlast 09 267 2772

Issued: October 2022

Users assume all risks and liability resulting from the use of this product and must confirm the suitability thereof by their own tests. Technical information contained herein is based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Conditions of Sale contain a limited warranty against manufacturing defects.