

Roberts 550 Adhesive Softener

Technical Data Sheet

PRODUCT DESCRIPTION:

Roberts 550 Adhesive Softener is a water dispersible solution designed to soften, loosen and assist in removing water based adhesives from subfloors and other surfaces. It is also useful for cleaning waterborne spray adhesives and coatings from guns and lines.

APPLICATION:

Roberts 550 Adhesive Softener may be applied to floor area by mop, ensuring that only an area capable of being worked in 10 - 15 minutes is dampened as, after this period, the adhesive will begin to harden. Use a scraper to lift adhesive from dampened surface. Following this, remove excess **Roberts 550** using water containing an alkaline detergent. Rinse thoroughly with clean water and allow to dry overnight before proceeding with floor covering installation.

For cleaning spray lines and guns, **Roberts 550** may be used as supplied, or diluted with warm water up to 1:1.

TECHNICAL DATA:

Typical Properties

Appearance:	Clear Liquid
Base:	Water dispersable Glycol
Viscosity:	Water consistency
Shelf Life:	Up to 1 year in sealed container at 20°C
Freezability:	Avoid freezing
Packaging:	20L / 5L

CAUTION:

Product is a skin irritant, wear gloves when using. **Roberts 550** contains solvent. Do not use in temperatures above 50°C as fumes may ignite under extreme circumstances.

SAFETY INSTRUCTIONS

Store inside in a well ventilated area away from oxidising agents and out of direct sunlight. Storage areas to be ventilated and kept below 50°C.

Refer to Local, State and Federal Regulations.

In use, please ensure that Occupational Health and Safety requirements are observed. Work area should be well ventilated and free of ignition sources. Prolonged skin contact or inhalation of vapours is advised against.

Safety Data Sheet available upon request.

Issued: July 2022

DGL Bondlast – Ph 09 267 2772

