

# Flexi-point

## Product Information

Flexi-point™ is a trowelable, custom coloured, permanently flexible adhesive that is used to point the ridge caps of cement & terracotta tiled roofs. It comprises water based organic polymers and mineral pozzolans that hydrate to form a strong yet flexible cement.

### PRODUCT FEATURES

- Flexes in harmony with normal roof movement
- Amazing bond strength
- Resists cyclonic wind uplift, C3 rated
- Outstanding UV Stability
- Fade resistant colour and long service life
- User friendly

Colour	Range available of 40 plus colours
Appearance when dry	Similar to coloured cement
Storage Temperature	Minimum 3°C, Maximum 40°C
Shelf Life (months)	12
Pack Size	10 L re-sealable plastic pail (volume content 16.5 Kg)

### ESTIMATION

Solids Content	88% ± 1
Dry film thickness	3-5 mm
Wet film thickness	3-5 mm
Theoretical Coverage	23-25 lineal metres per 10L pail.
Curing Time	2 hrs at 25°C and 50% relative humidity

### APPLICATION GUIDE & EQUIPMENT

Flexi-point™ parallels the traditional method for bedding and pointing tile roofs. Flexi-point™ should be applied at a uniform thickness of 3-5mm over a normal 4:1 yellow brick sand/cement bedding. The bedding cement should be finished plumb and free of large holes and voids, ensuring no bedding residue is left on the edge of the ridge cap bedding interface. Flexi-point™ may be applied over a fully cured bedding, or it can be applied over wet (just laid) bedding, but please allow additional curing time in this case.

Surface Preparation	Ensure a clean surface by removing all dirt, dust, grease and oil.
Product Preparation	Mix Flexi-point vigorously prior to use
Application Method	Round nose pointing trowel
Clean Up	Water

### PRECAUTIONS & LIMITATIONS

Recommendations on surface preparation and product application must be observed.

Curing Time	In temperate conditions of 25° C and 50% relative humidity the product may be expected to be rain resistant in around 2 hours of application. However, it should be noted that longer cure time is required when the product is applied over wet bedding, and where the temperature is below 15° C or relative humidity is above 70%.
-------------	---

For further technical information please phone Flexitech Pty Ltd – 1800 675 165  
A copy of the full official M.S.D.S can be found at [www.roofreviver.com.au](http://www.roofreviver.com.au)

ISSUE DATE – July 2022