

ROBERTS 6037

OUTDOOR GRASS CARPET ADHESIVE

GENERAL DESCRIPTION:

Roberts 6037 is an all-weather solvent based (flammable) adhesive specifically formulated for the outdoor installation of non-stretch open weave polypropylene backed synthetic grass carpet. Not recommended for urethane and E.V.A. backed carpets. Roberts 6037 develops high strength quickly and when cured will withstand unfavourable weather conditions. It will bond securely to cured concrete, asphalt, exterior grade wood and other clean paved surfaces and is ideal for use around swimming pools, balconies, outdoor recreational areas and other applications which are subject to moisture after fixing.

SURFACE PREPARATION:

To be in accordance with the Australian Standard 2455.1:2007 "Textile Floor Covering – Installation Practice". All surfaces to be bonded shall be dry, smooth, sound and clean.

APPLICATION:

Rough cut and lay out carpet according to manufacturer's instructions. Spread adhesive with the recommended notched trowel. Adhesive must be tacked up before floorcovering is lowered. Tack-up time will depend upon atmospheric conditions and can be determined by placing a small piece of floorcovering into the adhesive. When the floorcovering is pulled away, strings of adhesive should be apparent. If no tack or holding power has developed, wait five minutes re-checking every few minutes thereafter. Complete the installation according to floorcovering manufacturer's instructions. Do not allow heavy traffic for 24 hours. Do not use on rain or if rain is expected during or immediately after laying.

CLEAN UP:

To be in accordance with the Australian Standard 2455.1:2007 "Textile Floor Covering – Installation Practice". All surfaces to be bonded shall be dry, smooth, sound and clean.

TROWEL SIZES:

Smooth backed carpet/Smooth substrate: 2.4mm x 2.4mm x 2.4mm 'V' notched. Coverage up to 3.0m²/litre.
Textured backed carpet/Rough substrate: 3.2mm x 1.6mm x 3.2mm 'V' notched. Coverage up to 2.0m²/litre.
Heavily ribbed carpet/Rough substrate: 3.2mm x 3.2mm x 3.2mm "U" notched. Coverage up to 1.6m²/litre.

SAFETY AND HANDLING

This product is classified as **DANGEROUS**. Please refer to the relevant Material Safety Data Sheet for safety instructions. MSDS is available upon request. **HIGHLY FLAMMABLE** - Avoid contact with skin and eyes. Avoid breathing in vapour.

TECHNICAL DATA

Appearance: Brown Paste
Base: Synthetic Rubber
Solids: Approx. 58%
Viscosity: Trowllable mastic
Shelf Life: 12 months in sealed container
Dry Time:
Open Time:
Coverage: Up to 3.0m²/L
Pack Size: 20L / 4L tin
Heat Resistance:

Technical Data Sheet Version 3.0.1 (Rev. 04/21)

24-28 Lady Ruby Drive, East Tamaki, Auckland 2013, New Zealand

Bondlast NZ Ltd

Email: sales.bondlast@dglgroup.com Phone: (09) 267 2772

Website: www.bondlast.co.nz

Disclaimer: The information supplied is to the best of our knowledge true and accurate. The actual application of the product is beyond the manufacturers control. Any failure or damage caused by the incorrect usage of the product is not the responsibility of the manufacturer. The manufacturer insists that all workmanship must be carried out in accordance with AS 3958.1-2007. It is also the responsibility of the end user to ensure that the literature in their possession is the latest issue.